

TECHNISCHE SPEZIFIKATIONEN TYP 2000 (INNENVERZÄHNUNG)

Zeichnungsnummer	DI (mm)	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	nz	B/M (mm)	nn	B/M (mm)	t (mm)	O (mm)	U (mm)	A (mm)	C (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	b (mm)	T (kg)
2028.20.20.0-0.0414.00	414	518	326,5	56	490	375	8	18	12	M12	20	412,5	415,5	453	-	10,5	-	335	5	67	45,5	27,1
2030.20.20.0-0.0544.00	544	648	445,2	56	620	505	10	18	16	M12	20	542,5	545,5	583	-	10,5	-	456	6	76	45,5	36,9
2032.20.20.0-0.0644.00	644	748	547,2	56	720	605	12	18	18	M12	20	642,5	645,5	683	-	10,5	-	558	6	93	45,5	43,7
2034.20.20.0-0.0744.00	744	848	649,2	56	820	705	12	18	20	M12	20	742,5	745,5	783	-	10,5	-	660	6	110	45,5	51,1
2036.20.20.0-0.0844.00	844	948	737,6	56	920	805	14	18	20	M12	20	842,5	845,5	883	-	10,5	-	752	8	94	45,5	61,6
2038.20.20.0-0.0944.00	944	1048	841,6	56	1020	905	16	18	22	M12	20	942,5	945,5	983	-	10,5	-	856	8	107	45,5	65,8
2040.20.20.0-0.1094.00	1094	1198	985,6	56	1170	1055	16	18	24	M12	20	1092,5	1095,5	1133	-	10,5	-	1000	8	125	45,5	80,7

