

TECHNISCHE SPEZIFIKATIONEN TYP 7000 (AUSSENVERZÄHNUNG)

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
7000.30.20.0-1.1250.00	1461,6	1103	132	1355	1155	36	26	24	1280	1282	106	123	9	26	1428	12	119	+6	106	542
7002.30.20.0-1.1400.00	1635,2	1253	132	1505	1305	36	26	24	1430	1432	106	123	9	26	1596	14	114	+7	106	646
7004.30.20.0-1.1600.00	1831,2	1453	132	1705	1505	40	26	24	1630	1632	106	123	9	26	1792	14	128	+7	106	731
7006.30.20.0-1.1800.00	2044,8	1653	132	1905	1705	46	26	24	1830	1832	106	123	9	26	2000	16	125	+8	106	844
7008.30.20.0-1.2000.00	2236,8	1853	132	2105	1905	54	26	24	2030	2032	106	123	9	26	2192	16	137	+8	106	912

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
7020.30.25.0-1.1800.00	2076,8	1619	147	1925	1685	36	33	30	1836	1826	117	138	9	30	2032	16	127	+8	117	1126
7022.30.25.0-1.2000.00	2268,8	1819	147	2125	1885	44	33	30	2036	2026	117	138	9	30	2224	16	139	+8	117	1216
7024.30.25.0-1.2240.00	2516,4	2059	147	2366	2125	48	33	30	2276	2266	117	138	9	30	2466	18	137	+9	117	1378
7026.30.25.0-1.2500.00	2786,4	2319	147	2625	2385	54	33	30	2536	2526	117	138	9	30	2736	18	152	+9	117	1567
7028.30.25.0-1.2800.00	3096	2619	147	2925	2685	60	33	30	2836	2826	117	138	9	30	3040	20	152	+10	117	1785

