



TECHNISCHE SPEZIFIKATIONEN

TYP 4000

(AUSSENVERZÄHNUNG)

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
4016.30.25.0-0.1200.00	1378	1100	102	1290	1135	36	22	20	1223	1215	76	96	6	26	1350	10	135	+5,0	76	301
4018.30.25.0-0.1461.00	1648	1360	102	1555	1395	40	22	20	1484	1479	76	96	6	26	1620	10	162	+5,0	76	381
4020.30.25.0-0.1800.00	2001,6	1700	102	1890	1735	48	22	20	1823	1818	76	96	6	26	1968	12	164	+6,0	76	488

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
4022.30.30.0-0.1440.00	1653,6	1320	120	1545	1365	36	26	24	1469	1460	91	114	6	29	1620	12	135	+6,0	91	520
4024.30.30.0-0.1734.00	1953,6	1615	120	1845	1660	44	26	24	1763	1757	91	114	6	29	1920	12	160	+6,0	91	636
4026.30.30.0-0.2031.00	2253,6	1910	120	2140	1955	48	26	24	2060	2054	91	114	6	29	2220	12	185	+6,0	91	755
4028.30.30.0-0.2235.00	2457,6	2115	120	2345	2160	52	26	24	2264	2258	91	114	6	29	2424	12	202	+6,0	91	827

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
4030.30.35.0-0.1750.00	1985,2	1620	138	1860	1670	44	26	24	1784	1779	104	132	6	34	1946	14	139	+7,0	104	789
4032.30.35.0-0.1220.00	2461,2	2090	138	2335	2135	60	26	24	2254	2249	104	132	6	34	2422	14	173	+7,0	104	1019
4034.30.35.0-0.2620.00	2876,8	2490	138	2735	2540	60	26	24	2654	2649	104	132	6	34	2832	16	177	+8,0	104	1244

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
4036.30.40.0-0.2240.00	2524,8	2090	156	2375	2145	48	33	30	2272	2275	117	150	6	39	2480	16	155	+8	117	1316
4038.30.40.0-0.2619.00	2912,4	2465	156	2755	2520	52	33	30	2651	2654	117	150	6	39	2862	18	159	+9	117	1615
4040.30.40.0-0.2795.00	3096	2645	156	2930	2700	54	33	30	2827	2830	117	150	6	39	3040	20	152	+10	117	1723
4042.30.40.0-0.2915.00	3216	2765	156	3050	2820	60	33	30	2947	2950	117	150	6	39	3160	20	158	+10	117	1790
4044.30.40.0-0.3150.00	3456	3000	156	3285	3055	60	33	30	3182	3185	117	150	6	39	3400	20	170	+10	117	1969

