

TECHNISCHE SPEZIFIKATIONEN

TYP 4000

(INNENVERZÄHNUNG)

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
4050.20.25.0-0.1360.00	1460	1180	102	1425	1270	36	22	20	1337	1342	76	96	6	26	1190	10	119	-5,0	76	336
4052.20.25.0-0.1600.00	1700	1404	102	1665	1510	42	22	20	1577	1582	76	96	6	26	1416	12	1416	-6,0	76	405

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
4054.20.30.0-0.1381.00	1500	1164	120	1455	1275	36	26	24	1352	1358	91	114	6	29	1176	12	98	-6,0	91	474
4056.20.30.0-0.1630.00	1750	1416	120	1705	1525	40	26	24	1602	1610	91	114	6	29	1428	12	119	-6,0	91	558
4058.20.30.0-0.1800.00	1920	1568	120	1875	1695	48	26	24	1771	1777	91	114	6	29	1582	14	113	-7,0	91	643
4060.20.30.0-0.1995.00	2115	1764	120	2070	1890	48	26	24	1966	1972	91	114	6	29	1778	14	127	-7,0	91	716
4062.20.30.0-0.2330.00	2450	2100	120	2405	2225	54	26	24	2301	2307	91	114	6	29	2114	14	151	-7,0	91	839
4064.20.30.0-0.2538.00	2660	2228	120	2615	2430	60	26	24	2509	2515	91	114	6	29	2304	16	144	-8,0	91	963

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
4066.20.35.0-0.1960.00	2090	1722	138	2045	1850	52	26	24	1926	1931	104	132	6	34	1736	14	124	-7,0	104	851
4068.20.35.0-0.2500.00	2630	2254	138	2585	2385	66	26	24	2466	2471	104	132	6	34	2268	14	162	-7,0	104	1112
4070.20.35.0-0.2690.00	2820	2432	138	2775	2580	72	26	24	2656	2661	104	132	6	34	2448	16	153	-8,0	104	1225

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
4072.20.40.0-0.2199.00	2350	1920	156	2295	2065	52	33	30	2168	2164	117	150	6	39	1936	16	121	-8,0	117	1238
4074.20.40.0-0.2622.00	2770	2336	156	2715	2485	60	33	30	2590	2587	117	150	6	39	2352	16	147	-8,0	117	1495
4076.20.40.0-0.2950.00	3100	2646	156	3045	2815	60	33	30	2918	2915	117	150	6	39	2664	18	148	-9,0	117	1764
4078.20.40.0-0.3300.00	3450	3006	156	3395	3165	66	33	30	3268	3265	117	150	6	39	3024	18	168	-9,0	117	1935

TECHNISCHE SPEZIFIKATIONEN TYP 4000 (INNENVERZÄHNUNG)

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
4080.20.45.0-0.2940.00	3100	2656	175	3045	2800	66	33	30	2903	2900	132	168	7	43	2672	16	167	-8,0	132	1950
4088.20.45.0-0.3400.00	3560	3080	175	3505	3260	72	33	30	3363	3358	132	168	7	43	3100	20	155	-10,0	132	2435

Zeichnungsnummer	Dz (mm)	Dn (mm)	H (mm)	Lz (mm)	Ln (mm)	n	B (mm)	M (mm)	O (mm)	U (mm)	H1 (mm)	H2 (mm)	Hu (mm)	Ho (mm)	d (mm)	m (mm)	z	x.m (mm)	b (mm)	T (kg)
4082.20.50.0-0.2559.00	2725	2250	185	2670	2410	60	33	30	2522	2524	138	178	7	47	2268	18	126	-9,0	138	1892
4084.20.50.0-0.3520.00	3685	3200	185	3630	3370	78	33	30	3482	3485	138	178	7	47	3220	20	161	-10,0	138	2657
4086.20.50.0-0.3739.00	3905	3420	185	3850	3590	84	33	30	3701	3704	138	178	7	47	3440	20	172	-10,0	138	2823
4090.20.50.0-0.3839.00	4005	3520	185	395	3690	84	33	30	3801	3804	138	178	7	47	3540	20	177	-10,0	138	2905

